



RECOMMENDED
CABLE STRIPPING DIM'S

NO.	DESCRIPTION	MATERIAL	PLATING	Q'TY
1	BODY	BRASS	NICKEL	1
2	WASHER	FE	NICKEL	1
3	SPRING	SPRING STEEL	NICKEL	1
4	GASKET	PVC	RED	1
5	INSULATOR	PA	WHITE	1
6	RETAINER RING	ZINC	NICKEL	1
7	SHELL	ZINC	NICKEL	1
8	CONTACT PIN	BRASS	GOLD	1
9	FERRULE	BRASS	NICKEL	1

CUSTOMER NO		A±0.1	B±0.05	C±0.05	D±0.05
CBB-3210	RG/59U&62U	∅3.9	∅0.78	∅6.4	∅7.3
CBB-3211	RG/59UTEFLON	∅3.9	∅1.05	∅6.0	∅6.7
CBB-3214	RG/6U	∅4.9	∅1.20	∅7.6	∅8.1
CBB-3220	BELDEN 8281	∅5.3	∅1.05	∅8.2	∅9.1
CBB-3219	BELDEN 8218	∅2.7	∅0.5	∅4.6	∅5.3

				DESCRIPTION	3pc BNC Male Crimp Connector, 75 Ohm	SCALE	3/1	UNITS:MM	SRD ANGLE
				MODEL NO	CBB-32xx				
APPROVED	CHECKED	DRAWING	DESIGNED	DRAWING NO					
Wxp	Wxp	Hgh	Hgh	FINISHING		2015/03/12	A1		
				MATERIAL	SYE	DATE	REVISION		